



ÇİFT DİSKLİ GÜBRE SERPME MAKİNASI TWIN DISC FERTILIZER SPREADER

TÜRKAY, Çift diskli gübre serpme makinası, savurucu diskleri ve kanatları vasıtası ile gübreyi en uygun mesafeye dengeli ve düzgün olarak atabilen; böylelikle kullanılan gübre miktarından üst düzeyde faydalanabilmeyi sağlayan ideal bir makinadır. Mineral ve toz gübrenin koyulduğu yüksek kapasiteli depo, alt tarafında bulunan kapakların açıklığı ayar kolu ile değiştirilerek gübre normu ayarlanır. Çift diskli olması nedeni ile gübrenin tarla üzerindeki dağılımı daha iyidir. Gübre fırlatma mesafesinin uzun olması nedeni ile zamandan, dağılım düzgünlüğünün iyi olması nedeniyle de kullanılacak gübreden tasarruf sağlanır.

TÜRKAY Twin disc fertilizer spreader is an ideal machine that can broadcast the fertilizer by means of its winnowing disks and wings on ideal distance in a balanced and regular manner and in this way it provides the maximum benefit of the amount of fertilizer used. The fertilizer norm is adjusted by changing with the adjusting handle the opening of the lids at the bottom of the high-capacity tank where the minerals and powder fertilizer are placed. The distribution of the fertilizer over the farm is better because of the twin discs. As the distance where the fertilizer is broadcast is long, savings are made on the time and as the distribution uniformity is good, savings are made on the fertilizer to be used.



TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATION

		T-CDGS 800	T-CDGS 1000	T-CDGS 1200
Makina Kodu (Sipariş Numarası)	Machine code (Order number)	20801106	20801205	30801110
Depo Hacmi (Lt)	Capacity (Lt)	0,8 (m ³) / 800 Lt.	1 (m ³) / 1000 Lt.	1,2 (m ³) / 1200 Lt.
Toplam Genişlik (mm)	Overall Width (mm)	1680		1890
Toplam Uzunluk (mm)	Overall Length (mm)	1340		1400
Toplam Yükseklik (mm)	Overall Height (mm)	1030	1230	1320
Her Bir Diskte Kanat Sayısı	Number of Wings on Dispersing Discs	2		
Gübre Deposu Çıkış Delik Sayısı	Number of Openings on the Fertilizer Tank	2		
Makina Ağırlığı (kg)	Machine Weight (kg)	215	230	275
Kuyruk Mili Devir Sayısı (min-1)	P.T.O. Shaft Rotations (max) (min-1)	540		
Güç İhtiyacı (HP)	Required Tractor Power (HP)	35-40	40-45	50-55

Ölçü ve model değişimine hakkımız saklıdır. / We reserve our rights to make changes in designs, specifications and features without prior notice.